


B54-1054E TIRE - DEVELOPER, CPD



NOTES:

1. MATL:
FLANGES AND CORE: GRAY PVC
SPROCKETS & SCREWS: 316 CRES

QTY	PART OR POSITION NO.	NAME	DESCRIPTION - MATERIAL - FINISH
			X
			X
UNLESS OTHERWISE SPECIFIED:			SCALE: 1/1
1. DIMENSIONS ARE PER ANSI Y14.5-1973			DRAWN: MM 12/23/10
2. SURFACE ROUGHNESS PER ANSI B46.1-1978			ENGR: MICHELSON
3. LINEAR DIMENSIONS IN INCHES			APPR:
4. LINEAR TOLERANCES:			
.X ± .05, .XX ± .02, .XXX ± .005			
5. ANGULAR TOLERANCES:			
X ± 5°, XX ± 3°			
6. MACHINED SURFACES:			
I AND J ALL PLANES .002/INCH			
DIAMETERS WITHIN .005 TIR			
MAXIMUM SURFACE ROUGHNESS $\sqrt{32}$			
7. BREAK EDGES .01 TO .03			
8. FILLETS R0.02 MAX.			
REFERENCE DWG.			ASSY. - SPROCKET, CPD-1300
			SH 1 OF 1 C138-0100-1

THE INFORMATION DISCLOSED HEREIN IS THE EXCLUSIVE PROPERTY OF
TECHNICAL FILM SYSTEMS
OR MAY CONTAIN PROPRIETARY RIGHTS OF OTHERS AND IS NOT TO BE USED OR
DISCLOSED TO OTHERS WITHOUT THE WRITTEN CONSENT OF THE ABOVE