


B54-1054E TIRE - DEVELOPER, CPD



NOTES:

1. MATL:
 FLANGES AND CORE: PVC
 SPROCKETS & ASSY. SCREWS: 316 CRES

QTY	PART OR POSITION NO.	NAME	DESCRIPTION - MATERIAL - FINISH
			X
			X
UNLESS OTHERWISE SPECIFIED, 1. DIMENSIONS ARE PER ANSI Y14.5-1973 2. SURFACE ROUGHNESS PER ANSI B46.1-1978 3. LINEAR DIMENSIONS IN INCHES 4. LINEAR TOLERANCES: X ± .05, XX ± .02, XXX ± .005 5. ANGULAR TOLERANCES: X ± 5°, XX ± 3° 6. MACHINED SURFACES: I AND J ALL PLANES .002/INCH DIAMETERS WITHIN .005 TIR MAXIMUM SURFACE ROUGHNESS $\sqrt{32}$ 7. BREAK EDGES .01 TO .03 8. FILLETS R0.02 MAX.			SCALE: 1/1
DRAWN: MM 01-31-05			THE INFORMATION DISCLOSED HEREIN IS THE EXCLUSIVE PROPERTY OF TECHNICAL FILM SYSTEMS OR MAY CONTAIN PROPRIETARY RIGHTS OF OTHERS AND IS NOT TO BE USED OR DISCLOSED TO OTHERS WITHOUT THE WRITTEN CONSENT OF THE ABOVE.
ENGR: MICHELSON			
APPR:			ASSY. - SPROCKET, CPD-1300 (END)
REFERENCE DWG.			SH 1 OF 1 C138-0106-1