


B54-1054E TIRE - DEVELOPER, CPD



NOTES:

1. MATL:

FLANGES AND CORE: GRAY PVC
 SPROCKETS & SCREWS: C.P. GRADE II TITANIUM

QTY	PART OR POSITION NO.	NAME	DESCRIPTION - MATERIAL - FINISH
			X
			X
UNLESS OTHERWISE SPECIFIED:			SCALE: 1/1
1. DIMENSIONS ARE PER ANSI Y14.5-1973			DRAWN: MM 12/23/10
2. SURFACE ROUGHNESS PER ANSI B46.1-1978			ENGR: MICHELSON
3. LINEAR DIMENSIONS IN INCHES			APPR:
4. LINEAR TOLERANCES:			
.X ± .05, .XX ± .02, .XXX ± .005			
5. ANGULAR TOLERANCES:			
X ± 5°, XX ± 3°			
6. MACHINED SURFACES:			
I AND J ALL PLANES .002/INCH			
DIAMETERS WITHIN .005 TIR			
MAXIMUM SURFACE ROUGHNESS $\sqrt{32}$			
7. BREAK EDGES .01 TO .03			
8. FILLETS R0.02 MAX.			
			ASSY. - SPROCKET, CPD-1300 (END)
			SH 1 OF 1
REFERENCE DWG.			C138-0106-2

THE INFORMATION DISCLOSED HEREIN IS THE EXCLUSIVE PROPERTY OF
TECHNICAL FILM SYSTEMS
 OR MAY CONTAIN PROPRIETARY RIGHTS OF OTHERS AND IS NOT TO BE USED OR
 DISCLOSED TO OTHERS WITHOUT THE WRITTEN CONSENT OF THE ABOVE